LOOK FOR
YOUR CHOICES,
PICK THE BEST ONE,
THEN GO WITH IT



www.hellodmax.com info@dmax.biz





## **CONTENTS**

Multi Layer **SMART** 04

Multi Layer HYBRID 06

Multi Layer **OMEGA** 07

> **OMEGA** 08

**ALPHA** 09

**NATURA HT** 10

**NATURA OPAQUE** 11

Summary

12 **NATURA Z-ZIRCONIA** 

**COLORING LIQUID CLASSIC** 14

> **COZI** Stain System 16

**SUPER GREEN WAX** 18

**3D MAX** Printing Resin 19

> K Scan Spray 20

**EASY SCAN PEN** 21

**EASY SCAN POWDER** 21


TORNADO CAD/CAM 22

Miling Tools

DMAX Zirconia Surgical kit 23

> **EVERY CLEAN** 24

> > **ZIRFACE** 26





## **MULTILAYER SMART**

■ Multi layer Smart is a new concept zirconia block that allows users to get a natural gradation effect through different absorption rates of the upper and lower layers during the color liquid dipping

It is DMAX's best-seller that can innovatively reduce the inventory burden by creating 16 vita shades with simple dipping procedure.

- It is good for both anterior and posterior full crown- single and bridge- as it has sufficient strength as well as natural shade.
- To make the occlusal/incisal surface transparent, first brush with only one type of liquid, such as Enamel or Ice Gray or Ice Blue, and then dip it in the dentin color.



Innovative white multi layer block that can be made into all 16 vita shade multi layer blocks in combination with Dmax exclusive dipping liquid.

Time Saving: Create 16 vita shades with simple dipping

■ Great cost-saving solution for dental labs

There is no need to stock all 16 vita shade blocks, only smart block needs to be stocked.

1100 MPa 48% 16 vita shades available **SHADE A0** SMART DMAX Co.,Ltd www.hellodmax.com info@dmax.biz Tel:+82 53 592 3146 Made in Korea CLASSIC DIPPING LIQUID Zirconium Coloring Liquid ... Made in Korea \*Classic Dipping Liquid 16 VITA Shades

TRANSI UCENCY

Use effect liquid (Ice Blue, Ice Gray, Enamel) to achieve the appropriate effect.



Select the desired liquid for body and dip for 15 seconds, and then rinse with water for about 1 second.



After dipping, use a facial tissue to remove the remaining moisture



Dry using a dryer (200°C for 15 minutes)



200°C



FLEXURAL STRENGTH

15 minutes

Sinter under the condition of maintaining the maximum temperature of 1530°C for 2 hours.





1530°C



2 hours

## MULTILAYER HYBRID

## MULTILAYER OMEGA

- Multi Layer Hybrid is a zirconia block with excellent strength and transparency. It is a full crown block with natural gradation effect created through multiple layers with different transparencies from 1200 MPa in the lower layer to 800 MPa in the upper layer.
- All 16 vita shades are available.

■ Due to the high transparency of the occlusal/incisal surface and the natural shade of the margin part, anyone can create a satisfactory full crown without coloring.

You just need to select a pre-shaded block from 16 vita shades, mill the crown and sinter it, so no coloring is required. It saves a significant amount of time and work required for coloring and drying.



TRANSLUCENCY FLEXURAL STRENGTH
45~51% 800 ~ 1200 MPa

All 16 Vita shades



■ Multi Layer Omega is a multi-layer block optimized for anterior full crown with excellent transparency and natural gradation.



■ The strength of 800MPa relatively weak, but compared to other highly transparent dental materials such as glass or resin, it is strong. You can get the great results with just a little stain glazing after sintering instead of coloring work. If you add a little coloring work, you can get even better results. Can be used for up to six anterior bridges.



## OMEGA

- Omega is a zirconia block dedicated to the anterior full crown and inlay which has high degree of transparency.
- Despite its high transparency, it has a good strength of 800MPa.



- Alpha is DMAX's best-selling zirconia block. It has a very strong strength of 1200MPa while still maintaining excellent transparency and shade. Suitable for any case. Since it is a pre-shaded block, anyone can create an excellent full crown with minimal coloring work.
- All 16 vita shades are available.





## NATURA HT


■ Natura HT zirconia block is suitable for coping as it has the highest strength of about 1300 MPa. The superior strength and mild transparency make it suitable for anatomic coping bridge which need cutback design.



1300 MPa

SHADE AO





## OPAQUE NATURA

- Natura Opaque is the most opaque zirconia block among DMAX's zirconia blocks. ■ It is suitable for implant coping as its strength is 1300 MPa.
  - Can be used to block out the discolored teeth or metal color
  - Suitable for making zirconia link abutments



## CLASSIC 30ml EFFECT LIQUID

- If you use liquid before sintering, a more natural effect can be achieved on occlusal/incisal surface.
- A good control of the liquid can maximize the aesthetic control of the zirconia prosthesis.

# Brown Ice Blue Orange Brown Blue Orange Yellow Dark Blue Fluorescence Ice Gray White Dark Gray

Enamel

Pink

## CLASSIC 30ml BRUSHING LIQUID

- Can be used for other brands zirconia block
- All 16 vita shades

### TIPS FOR COLORING

### 1. Check the block color first

Please check the color of the block carefully before using the coloring liquid on a pre-shaded block.

### 2. Dipping technique

With dipping liquid, you can easily get the color you want. For example, if you use A1 shade block, you can use A1 shade liquid to make A2 color crown before sintering. Additional coloring can be done after sintering to match shade in more detail.

### 3. Brushing technique

Brushing method is basically the same technique used for porcelain build up and staining.

DMAX's special liquids are a unique solution for making natural-looking crowns.

## 4. Bridge cases

To get the same color on the pontic area, brush with water once, then follow the same steps with dipping or brushing. Otherwise, pontic can be little darker than regular crown or coping area because of thick volume.



## **CLASSIC** 100ml **DIPPING LIQUID DMAX** CLASSIC DIPPING LIQUID ....

Dipping Liquid is used with the Multi Layer Smart block, and this is unique method and know-how of DMAX.

Because the absorption rate of the upper and lower layers is different, a natural gradation effect can be achieved.

16 vita shades can be implemented with simple dipping, which can innovatively reduce the inventory burden, and even unique color cases can be made faster and easier by dipping in desired color from 1 second to 15 seconds.

All 16 vita shades



**B** Shade

C Shade



2mm thick sample taps are sintered after dipped into base color liquid for 15sec & dried. no glazing or polishing applied.



### ■ WHAT IS COZI STAIN SYSTEM

- Micro build up
- Stain for Zirconia

## ■ COZI STAIN SYSTEM BOX:

**Product Component** 25 kinds of color pastes Exclusive liquid 2ea

## ■ ADVANTAGE OF COZI STAIN SYSTEM







Raise of Temp.

Holding Temp. **50** ℃ 2min.

**Dry Time** 5min.

Final Temp.

**Vacuum Start** 

**Vacuum Stop 500℃ 900℃** 

## **SINTERING PROGRAM FOR COZI**

Start (°C)	Dry/ Pre Heat (min)	Heat Rate ( <sup>0</sup> C/min)	High Temp ( <sup>0</sup> C)	Hold (min)	Vacuum start ( <sup>0</sup> C)	Vacuum stop ( <sup>o</sup> C)
500	5	50	800 ~ 900	2	500	800 ~ 900

## ■ SAMPLE CASE COZI BASE MIDDLE INCISAL Mamelon Light Shade A Light Unripe Mango Mamelon Light Smart Block A1 dipping Shade A Medium Mamelon Light Unripe Mango Mamelon Light Unripe Mango Mamelon Light Shade A Dark Mamelon Light Illusion

## **DENTIN SHADE**

## Shade A Light (VITA shade A1)









### **CERVICAL GROOVE & EFFECT**

## Mamelon (Ivory Yellow)

Spicy Curry (Reddish Yellow,

## (+) Shade A= Shade B) **Unripe Mango**

(Green Yellow, (+) Shade A= Shade B)

### Lemon Yellow (Very Strong Light Yellow)

Maroon Five (Kaki Brown, Groove & Crack Line)

### Red Brown (Orange Red Brown, Groove & Cervical)

Dark Brown (Dark Brown, Groove & Crack Line)

## **INCISAL TRANSFER**

### Illusion (Jade Green, Middle of Incisal)

Blue Light

**Gray Light** 

(Incisal)

(Side of Incisal,

(+) Natural Glaze

= more transfer)







**GINGIVAL & EFFECT** 





**SPECIAL** 

**OPAQUE & INCISAL** 

Mamelon Light

Snowy White

Halo

(Incisal)

(Ivory white, Transfer, Increase brightness, Incisal)


(Opaque white, Increase

brightness, Incisal)



(Glaze, Low chroma, High Transfer)

> Add on Glazing (Modify)



## **SUPER GREEN WAX**

### System:

Amann Girrbach Dentium RND ARUM I-Mes I-Core VHF Cerasys Katana Wieland Cerec Origin Yena Charley Protech Zirkonzahn Dentaim Roland


Thickness:

 10mm
 16mm
 22mm

 12mm
 18mm
 25mm

 14mm
 20mm





- Wax Block for casting is optimized for the milling process
- DMAX wax block is perfectly compatible with the jig used in processing of zirconia





## **3D MAX** Printing Resin

## 3D MAX- Crown

- For permanent crown, inlay and onlay.
- Natural translucent color
  High strength and wear resistance
  A1,A2,A3,A3.5 shade is provided

## **3D MAX-TEMP**

- For temporary crown and bridge
- Natural translucent color A1,A2,A3 shade is provided
- Flexural strength is more than 50MPa (ISO 10477)

## 3D MAX-SG

- For implant surgical guide
  Easy to operate because the
  material is transparent
- Sterilization with autoclave possible
- High precision printable materials allow for precision surgery







## **3D MAX PRINTING RESIN**

Dental materials for 3D printing
Biocompatible materials
High precision printable materials
Light curing resin for DLP/SLA 3D Printer with
a light spectrum of 385-405nm





## K SCAN SPRAY

- K SCAN SPRAY is the most thin anti-light reflection spray for dental CAD/CAM scanning
- Non flammable



Easily removed by steam cleaner

Best choice for custom abutment scan

Guarantee the best fit of zirconia crown and custom abutment



Better price with amount of 200g



No need for thick application
Thin application over
several times is more
effective than one-time
thick application

With K Scan, Reduce the working dust!

Reduced dust by 50% compared to existing product, using special solvents

## PRECAUTIONS

Do not store in temperature above  $40^{\circ C}$ Use ventilation when used in a closed room Do not dispose into fire and keep it in a closed place.








## **EASY SCAN PEN**

10ml



Non flammable

## **HOW TO USE**

- Please shake well before use. For the first use, press pen point 5-10 times until pen tip get moisturize by liquid
- If the pen point gets dry during use, gently press the pen tip 1-2 times. Do not shake the pen after pressing the pen point. Liquid could splatter from the pen.
- Close the lid of the pen when it is not in use. Liquid may leak if the lid is open.

## **EASY** SCAN POWDER

10g



- Easy Scan powder is a powder-type scan coating for the preparation of CAD/CAM scan.
- Non flammable

## **HOW TO USE**

- Brush or gently pat the powder to the object.
- The build up could become broken if patted with strong impact





## TORNADO CAD/CAM MILING TOOLS




- Maintain a high-precision form even during long-term use
- Long life with new diamond coating technique (our own technology)
- Applied unique design technology
- Chip exhausted smoothly in working
- Tool shape is designed for diamond coating
- Use for zirconia and hybrid resin
- Round shape designed for smooth chip exhaust.
- Sharp edge for fast cutting

## **Diamond** Coating Tools







Fracture view of diamond coating

## **TIN** Coating Tools

- Aluminum Titanium Nitride
- Use for Wax, PMMA, Zirconia
- Cutting in extreme condition material Good abrasion resistance Good corrosion resistance



## DMAX tools can be used on any of the following systems

## **■ PRO-DEN DENTAIM**

Diameter	Coating	Shank
D0.6	TIN	6
D1.0	TIN	6
D2.0	TIN	6
D0.6	DIA	6
D1.0	DIA	6
D2.0	DIA	6

### AMANN

D0.3	DLC	3
D0.6	DIA	3
D1.0	DIA	3
D2.5	DIA	3

## ■ ARUM-100

D0.6	TIN	6
D1.0	DIA	6
D2.0	DIA	6

## ■ ZIRKONZHAN M1 (TITAN)

D2.0		6
D3.0		6
SIRONA		

D1.0	DIA	3
D2.5	DIA	3

## RND

Diameter	Coating	Shank
D0.6	DLC	6
D1.0	D <b>I</b> A	6
D2.0	DIA	6
D0.6	DIA	3
D1.0	DIA	3
D2.0	DIA	3

## **CHARLY**

D0.5	TIN	3
D1.0	DIA	3
D1.5	DIA	3
D3.0	DIA	3

## ■ ARUM-150

D0.6	TIN	4
D1.0	DIA	4
D2.0	DIA	4

## **■ IMES ICORE**

D0.6	TIN	3
D1.0	DIA	3
D2.5	DIA	3

## **ROLAND**

Diameter	Coating	Shank
D0.6	TIN	4
D1.0	TIN	4
D2.0	TIN	4
D1.0	DIA	4
D2.0	D <b>I</b> A	4

## **ZIRKONZHAN M5**

D1.0	DLC	3
D2.0	DLC	3
D1.0		3
D2.0		3

## ■ ARUM (TITAN)

D1.5	6
D2.0	6
D3.0	6

## MANIX (TITAN)

D2.0	6
D3.0	6

## **DMAX ZIRCONIA**

## Superior abrasion resistance Much longer life time than metal drill SURGICAL KIT

- Excellent corrosion resistance No rust, chemically stable
- Biocompatible materials There is no allergic reaction
- Low thermal conductivity Minimize bone necrosis due to low frictional heat
- After 30 times drilling, bone area heating test



TrimRite Surgical Drill



0 times drilling



30 times drilling



Zirconia Surgical Drill



0 times drilling



100 times drilling



## **EVERY CLEAN**

The heating element of the sintering furnace used for a long time are easily oxidized due to the deposition of residues of the coloring liquid generated during sintering.

The pale green light from the prosthesis after sintering is due to the phenomenon that the contaminants deposited on the heating element are colored on the zirconia prosthesis.

Sintering furnace contamination is one of the causes of discoloration after sintering of zirconia prostheses.

Every Clean absorbs and removes contaminants inside the sintering furnace, so it helps users get the best sintering results.

Routine cleaning of the sintering furnace according to instructions can prolong the longevity of the heating element as well as prevent pollution within the sintering furnace.

Every Clean consists of 12 bottles (100g each) with different marks for each month so that cleaning can be done on a monthly basis.





## ORGANIZATIONAL CLEANING



Put date of cleaning on Everyclean tag enclosed in box and then hang/keep it on handle of sintering furnace, which enables you to do monthly cleaning.

## Instructions

STEP 1 Apply 50g of Every Clean on the sintering crucible and spread them wide and even.






If the sintering crucible has a bead, make sure to remove the bead before applying Every Clean.

## STEP 2

- For 2 hours, raise the temperature from room temperature to 1580 degrees, and then keep it at 1580 degrees for 30 minutes.
- After holding for 30 minutes, lower the temperature to room temperature for 2 hours.



## STEP 3




If the inside of the sintering furnace is clean and free from pollutants, Every Clean will have turned from orange to white.






## ZIRFACE

- Zirface can resolve the disadvantages of ETCHING which are strong smell and long working time.
- It does not harm the health of users.




## **NANO TECHNOLOGY**

Maximizes adhesion by large surface area by forming Micro Surface Irregularity (Roughness)



Zirconia with sintered state

The zirconia surface treated with ZIRFACE is coated with nano-sized zirconia particles (ZrO<sub>2</sub> Particles) to form a porous surface



When the resin cement is applied, the porous surface and the resin cement are combined to maximize the adhesion of the zirconia prosthesis.

## How to Use ZIRFACE

the inner surface of the zirconia

prosthesis using air.

Hemove foreign substances from

Shake the container well

Shake the container well about 10 times to mix the sediment in the container before use.




Apply once without any space on the inside of the prosthesis using a brush.



## **IMPROVED BONDING STRENGTH**

According to the surface treatment study, the group to which ZIRFACE was applied showed a value 4 to 9 times higher bonding strength than that of the control and acid.



## **IMPROVED SURFACE ROUGHNESS**

According to the surface treatment study, the group to which ZIRFACE was applied showed a surface roughness value 2 to 6 times higher than that of the control and acid.











## **Korea Head office**

37-26, Dasa-ro 71-gil, Dasa-eup, Dalseong-gun, Daegu, Korea info@dmax.biz 82-53-592-3146 www.hellodmax.com

## Korea Gwangju office

#206, 249, Chuam-ro, Buk-gu, Gwangju, 61003, Korea info@dmax.biz 82-62-602-0844 www.hellodmax.com

## **America office**

14747 Artesia Blvd., Suite 5A La Mirada, California 90638 info@dmaxamerica.com 714-752-6073 www.dmaxamerica.com

## Vietnam office

67 Yen The, Ward 2, Tan Binh District, HCMC, Vietnam info@hellodmaxasia.com 84-902-915-830 www.hellodmaxasia.com

